



Cold Pour Crack Fill

#315

Cold Pour Crack Fill #315

Goldstar #315 Cold Pour Crack Filler is your solution to enhancing the integrity of asphalt pavement by sealing existing asphalt cracks, which protects the underlying subgrade from premature deterioration and costly structural repairs. When applied before sealcoating using Goldstar's premium Goldcoat HP#310 sealcoat, Goldstar #315 crack filler reduces the appearance of cracks in your asphalt surface further beautifying and protecting your asphalt pavement.



Easy to Use

Goldstar #315 Cold Pour Crack Filler (RTU) ready to use from the bucket. Easy and safe to install; Quickly and easily fill thousands of feet of cracks in hours. Perfect for owners looking to reduce their asphalt maintenance budget by self-performing their basic asphalt maintenance needs.

Goldstar #315 Cold Pour Crack Filler performs well in all climates. It is engineered to withstand pavement expansion and contraction.

Goldstar #315 Cold Pour Crack Filler is available in individual 1-gallon containers, 5-gallon buckets, 36-bucket pallets, 55-gallon drums & 250-gallon totes.



Scan to see all products and services

www.GoldStarAsphalt.com
Info@GoldStarAsphalt.com
T +1 888 770 7325





Cold Pour Crack Fill

#315

Cold Pour Crack Fill #315

- DESCRIPTION:** Cold Pour Crack Filler is (RTU) ready to use from the bucket. Easy and safe to install. Quickly and easily fill thousands of feet of cracks in a matter of hours. Perfect for owners looking to reduce their asphalt maintenance budget by self-performing their basic asphalt maintenance needs.
- FEATURES & BENEFITS:** Used on parking lots, airports, streets, playgrounds, etc. Cold Application: No heating necessary. Apply right from the container. Great for hot or cold climates. Easy to apply. No fancy tools or experience is necessary. In a few hours, you can fill thousands of feet of cracks.
- WEATHER LIMITATIONS:** For best results, apply on dry surface when the temperature is not expected to drop below 50 F for the next 24 hours. Extraneous amounts of water will destroy this crack filler if it has not been cured for at least 8 hours.
- SURFACE PREPARATION:** The surface must be dry. Blow or sweep out cracks, removing all vegetation, dust, and other debris.
- COVERAGE:** 120 linear feet 1/4" wide by 1/4" deep per gallon. Coverage will vary with the size and depth of cracks.
- APPLICATION:** Stir before using. It may be applied with pour pots or a suitable crack-sealing applicator. Fill cracks before the material sets up, and remove excess from the surface using rubber squeegees. A second application may be necessary for deep cracks or joints. If seal coating before complete drying or set up of crack sealer, sprinkle silica sand (lightly) to promote adhesion to seal coat sealant.
- DRYING TIME:** Tack free in 1 hour. Lightly sand in immediate traffic areas. Dry in 4 - 24 hours, depending on weather conditions and thickness of material (except in cases of extreme humidity).
- CLEAN UP:** Wash tools in water. Use paint thinner if hardened.
- STORAGE:** CAUTION - keep from freezing. Do not store in direct sunlight or where temperatures exceed 100 F.
- PACKAGING:** Cold Pour Crack Filler is available in 1-gallon containers, 5-gallon buckets, 36-bucket pallets, 55-gallon drums & 250-gallon totes.
- COLOR:** Dark Brown - Black



Scan to see all
products and
services

www.GoldStarAsphalt.com
Info@GoldStarAsphalt.com
T +1 888 770 7325

