

GoldStar Oil Seal

#330

Oil Seal #330

Ready to use latex-based primer designed to prime existing oil and grease spots before asphalt pavement sealcoating. Oil Seal #330 ensures adherence between existing asphalt and the applied sealcoat while preventing oil, gas, and other petroleum-based substances from migrating through newly sealed asphalt pavement.





Each gallon of GoldStar Oil Seal #330 is manufactured at Goldstar Asphalt Products manufacturing facility in Perris, CA. Goldstar's facility has the latest technology, ensuring consistency in every Oil Seal #330 batch.



Use GSA Oil Seal on oil stains before sealcoating



Scan to see all products and services

www.GoldStarAsphalt.com Info@GoldStarAsphalt.com T + 1 888 770 7325





GoldStar Oil Seal

#330

Oil Seal #330

DESCRIPTION: Ready to use latex-based primer designed to prime existing oil and grease spots before asphalt

pavement sealcoating. GSA Oil Seal #330ensures adherence between existing asphalt and applied sealcoat while preventing oil, gas, and other petroleum-based substances from migrating through

newly sealcoated asphalt pavement.

SURFACE Surface areas must be free from dirt and dust before treatment. Scrape excessive build-up of oil, grease,

PREPARATION: or any other chemical stain spots. Lightly burn off excessive build-up.

APPLICATION: Mix well before using. (RTU) ready to use on heavy oil spots, grease, and other stains. GSA Oil Stain

#330 can be applied with a suitable spray machine, push broom, brush, or roller.

COVERAGE: 100-200 square feet per gallon.

CLEAN UP: Wash tools in water. Use a suitable paint thinner if the material has dried.

STORAGE: Keep from freezing. Do not store in direct sunlight or where temperatures exceed 100F. The container

should be closed when not in use. Keep out of the reach of children.

PACKAGING: Available in 5-gallon buckets and 55-gallon drums.

COLOR: Black



