



GoldStar Tack

#325

Tack SS-1H #325

GoldStar #325 Tack is a premium SS1H material. GoldStar #325 Tack allows proper bonding between asphalt lifts, repairs, and existing road surfaces. Inadequate bonding between layers can result in delamination, which causes wheel path cracking, fatigue cracking, potholes, and asphalt rutting, significantly reducing pavement life. Applying GoldStar #325 Tack is a critical step during asphalt construction, ensuring structurally sound pavement layers that will pass the test of time. When applied to aged and oxidized asphalt pavement surfaces, GoldStar #325 Tack acts as a rejuvenating agent, protecting and extending the life of your asphalt pavement surfaces.



Delivery or Bulk Loadout

- 6,000 Gallon GoldStar #325 Tack Holding Tank for on-site bulk material loadout.
- 1,500 Gallon Rosco Maximizer 3 Tack Distribution Truck available for rent.
- 5 Gallon Buckets available for pickup or delivery, individually or palletized for your convenience.



Scan to see all products and services

www.GoldStarAsphalt.com
Info@GoldStarAsphalt.com
T +1 888 770 7325





GoldStar Tack

#325

Tack SS-1H #325

- DESCRIPTION:** An anionic Petroleum asphalt-based product bonds fresh asphalt paving material and existing asphalt or concrete material. Also used to rejuvenate old asphalt pavements.
- FEATURES & BENEFITS:** It creates a solid and long-lasting bond that helps prevent water and other liquids from reaching the pavement structure.
- MATERIAL PREPARATION:** When used as a binder, preparation is optional. When used to rejuvenate pavement, less than 50% water should be added to the material for dilution. You may need to heat the material to liquify it.
- APPLICATION:** This should be done by means of a distribution truck, tack rig, or tack broom. All can be purchased or rented through GoldStar Asphalt Products.
- WEATHER LIMITATIONS:** Application should be postponed if wet or freezing weather is expected 24 hours before or following the application. On hot days, pavement should be misted with a fog system before application.
- COLOR:** Jet black color upon drying.
- CLEAN UP:** Use warm water with an emulsifying cleaner.
- STORAGE:** Keep from freezing. Do not store in direct sunlight or where temperatures exceed 100F.
- PACKAGING:** Onsite bulk material loadout. 5 Gallon Buckets are available for pickup or delivery, individually or palletized, for your convenience.



Scan to see all
products and
services

www.GoldStarAsphalt.com
Info@GoldStarAsphalt.com
T +1 888 770 7325

