

SealCoat Defender

Additive #341

SealCoat Additive #341

Goldstar #341 SealCoat Defender is a sealcoat additive designed to enhance the performance of any manufacturer's sealcoat product. Goldstar #341 SealCoat Defender boosts sealcoat's resistance to water, gas, and oil while strengthening the bond between the sealcoat and the existing asphalt surface. This enhanced bond significantly reduces wet-track abrasion test results; this will reduce power steering marks, minimize rock shine, and overall extend the life of your asphalt sealcoat.





Increase SealCoat Durability

Goldstar #341 SealCoat Defender is the additive of choice for forward-thinking contractors and owners looking to increase sealcoat durability and extend the life of their sealcoat application in high-traffic environments. Adding Goldstar #341 SealCoat Defender to your sealcoat of choice is a sure way to save money by decreasing the frequency of future sealcoat applications.



Scan to see all products and services

www.GoldStarAsphalt.com Info@GoldStarAsphalt.com T +1 888 770 7325





SealCoat Defender Additive #341

SealCoat Additive #341

DESCRIPTION: Goldstar #341 SealCoat Defender is a sealcoat additive designed to enhance the performance of any manufacturer's seal coat product.

FEATURES & BENEFITS:

Goldstar #341 SealCoat Defender boosts sealcoats' resistance to water, gas, and oil while strengthening the bond between the sealcoat and the existing asphalt surface. This enhanced bond significantly reduces wet-track abrasion test results. This will reduce power steering marks, minimize rock shine, and extend the life of the asphalt sealcoat.

APPLICATION: Mix 2-3% of Goldstar SealCoat Defender to diluted asphalt sealcoat. It is best when introduced to an agitated sealcoat tank. Dilute and apply the amended sealcoat per the manufacturer's recommendation. For

best results, use with Goldstar HP #310 GoldCoat SealCoat.

WEATHER LIMITATIONS:

Follow asphalt sealcoat manufacturers' recommendations.

COLOR: Dries black when mixed with premium asphalt sealcoats.

CLEAN UP: Wash tools in water.

STORAGE: Keep from freezing. Do not store in direct sunlight.

PACKAGING: 5-gallon bucket



Scan to see all products and services



